

RL1001 waterproof temperature transmitter



1000 Series

Part of the RL1000 range, the RL1001 waterproof temperature thermister is a sealed single thermister transmitter with a 25mm long fixed probe

Features

- ✓ Radio system is fully approved and exceeds all specifications enforced by relevant national authorities
- ✓ System complies with the European R&TTE Directive, which covers EMC and radio specifications
- ✓ A 'battery low' indication is displayed via PC software, warning of the requirement for battery change prior to power loss
- ✓ Software flags alert in the event of total transmission failure



Product code: RL1001-434.075 (other frequencies are available)

Instrumentation specification	
Dimension	167 x 40mm diameter
Weight	200 grams
Power supply	3.6V AA Lithium battery
Battery life	Up to 2 years (dependent on conditions of use and instrument settings)
Case material	Acetal
Instrument operating range	-35°C to +60°C
IP Rating	IP68
Accuracy	+/- 0.2°C between -10°C to +40°C +/- 0.3°C outside these extremes
Long term drift	< 0.1°C per year

Radio transmitter functions	
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.
Radio power	10mW
Radio range	3km over open ground
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Hardware required	CR2 / CR3 – Controller SR2 – Smart Receiver REP – Repeater

Product codes	
88706	AA Lithium battery
Probe options	Please refer to the Hanwell Pro Sensor datasheet

Manufactured by Hanwell | Ellab RoHS

Version 3 - EC190194

Disclaimer: The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product may be changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales@hanwell.com