

FW01

GSM Transmitter

Part of the **Flood Series**, the FW01 GSM FloodWatch* unit is an SMS flood alarm monitor with single flood detection and flood cable.

*For use in the UK and Europe only

Product Features

- ✓ High performance technology with advanced flood detectors
- ✓ Superior performance hardware with flood cable
- ✓ Easily accessible battery and USB socket
- ✓ Complies with RoHS, EU directives and WEEE
- ✓ Carries CE Marking

Typical Applications

- Buildings in close proximity to rivers
- Museums
- Housing associations



Flood



Leak



Product code: FW01

Instrumentation specification	
Dimensions	200 x 120 x 80mm
Weight	950g
Power supply	5 x 1.5V Alkaline C cells battery (recommended option) 12V DC (regulated power supply) connection 2.1mm Jack
Case material	ABS
Battery Life	Up to 2 years (dependent on conditions of use)
Instrument operating range	-20°C to +60°C in a non-condensing RH environment

Technical Specifications		
Product Sensor	VO53	Flood Cable (supplied by the meter)
Input Channels	4	

GSM functions	
Network capability	For use on GSM networks at 850MHz to 1900MHz (Quad Band)
Aerial Connection	SMA Socket
Aerial type:	Stubby straight/right angle and remote mount on 2mtrs cable
Software included	Configuration Utility

Accessories	
VO53	Flood Cable (supplied separately by the meter)
G16	DC power supply
G17	UK power cord

Manufactured by Hanwell | Ellab RoHS

Version 2 - EC190194

Disclaimer: The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product may be changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales@hanwell.com