

ML4114 Radio Transmitter

Pro ML4000RH/T Series

Part of the **Hanwell Pro** ML4000RHT Series, the ML4114 combines high accuracy temperature and humidity measurement using an EE07 probe. The instrument includes LCD display and 434.075MHz frequency as standard.

Features

- ✓ Combined temperature & humidity measurement
- ✓ LCD display with 50,000 data readings per channel & up to 2 years battery life
- ✓ Superior performance hardware & high accuracy sensors
- ✓ Easily accessible battery & USB socket
- ✓ Low power radio for long distance transmission (3km over open ground)
- ✓ Complies with RoHS, EU & WEEE directives
- ✓ Carries CE Marking

Typical Applications

- Dry storage
- Ambient room conditions


Always ask for a long-range signal strength test.



We can prove ours to be unrivalled.



Product code: ML4114-434.075



Instrumentation specification	
Dimension (Excl. ancillaries)	110 x 80 x 35mm
Weight	200 grams
Power supply	1 x 3.6V AA Lithium battery
Battery life	Up to 2 years (dependent on conditions of use and instrument settings)
Case material	ABS & PC
Memory capacity	50,000 readings per channel (unit will wrap when full)
Clock accuracy (logging)	20 ppm at 25°C
IP Rating	IP30
Instrument measuring range	-20°C to +60°C if using an integral, onboard, probe -40°C to +60°C if using a compatible external probe, connected via an extension cable
Instrument operating range	-20°C to +60°C in a non-condensing RH environment
Instrument storage temperature	-40°C to +60°C
Resolution	0.1°C (temp), 0.1%RH (humidity)

Radio transmitter functions	
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.
Radio power	10mW
Radio range	3km over open ground
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Software compatibility	EMS - All Versions Synergy - All Versions RadioLog 8
Hardware required	CR2 / CR3 – Controller SR2 – Smart Receiver REP – Repeater

Product codes	
88706	AA Lithium battery
Y119	Wall mounting bracket
Probe options	Please refer to the Hanwell Pro Sensor datasheet