

# ML4114 Radio Transmitter

## Pro ML4000RH/T Series

Part of the **Hanwell Pro** ML4000RHT Series, the ML4114 combines high accuracy temperature and humidity measurement using an EE07 probe. The instrument includes LCD display and 434.075MHz frequency as standard.

### Features

- ✓ Combined temperature & humidity measurement
- ✓ LCD display with 50,000 data readings per channel & up to 2 years battery life
- ✓ Superior performance hardware & high accuracy sensors
- ✓ Easily accessible battery & USB socket
- ✓ Low power radio for long distance transmission (3km over open ground)
- ✓ Complies with RoHS, EU & WEEE directives
- ✓ Carries CE Marking

### Typical Applications

- Dry storage
- Ambient room conditions

Always ask for a long-range signal strength test.



We can prove ours to be unrivalled.

Instrumentation specification	
Dimension (Excl. ancillaries)	110 x 80 x 35mm
Weight	200 grams
Power supply	1 x 3.6V AA Lithium battery
Battery life	Up to 2 years (dependent on conditions of use and instrument settings)
Case material	ABS & PC
Memory capacity	50,000 readings per channel (unit will wrap when full)
Clock accuracy (logging)	20 ppm at 25°C
IP Rating	IP30
Instrument measuring range	-40°C to +80°C
Instrument operating range	-20°C to +60°C in a non-condensing RH environment
Instrument storage temperature	-40°C to +60°C
Resolution	0.1°C (temp), 0.1%RH (humidity)



Product code: ML4114-434.075

Radio transmitter functions	
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.
Radio power	10mW
Radio range	3km over open ground
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Hardware required	CR2 / CR3 – Controller SR2 – Smart Receiver REP – Repeater

Product codes	
88706	AA Lithium battery
Y119	Wall mounting bracket
Probe options	<a href="#">Please refer to the Hanwell Pro Sensor datasheet</a>

Manufactured by Hanwell | Ellab RoHS

Version 5 - EC190194

**Disclaimer:** The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product may be changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales@hanwell.com