

# RL407 transmitter

## Pro Bug Series

Part of the Hanwell Bug series, the RL407 includes internal temperature sensor within a slimline transmitter for discreet or space restricted monitoring.

### Features

- ✓ Wireless transfer
- ✓ Internal temperature sensor
- ✓ High performance technology
- ✓ Low power radio for long distance transmission (1km over open ground)
- ✓ User accessible battery
- ✓ Complies with RoHS, EU and WEEE directives
- ✓ Carries CE Marking

### Typical Applications

- Fridges
- Freezers
- Chillers

Always ask for a long-range signal strength test.



We can prove ours to be unrivalled.

Instrumentation specification	
Dimension (Excl. ancillaries)	105 x 65 x 19mm
Weight	100 grams (without battery)
Power supply	2 x AAA Alkaline battery
Case material	ABS
IP Rating	IP30
Instrument operating range	-10°C to +55°C
Storage temperature	-40°C to +60°C
Accessories	
Y125	Wall mounting bracket
88715	AAA Alkaline battery



Product code: RL407-434.075 (other frequencies are available)

Radio transmitter functions	
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.
Radio power	10mW
Radio range	1km over open ground
Battery life	Up to 1 year (dependent on conditions of use and instrument settings)
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Hardware required	CR2 / CR3 – Controller SR2 – Smart Receiver REP – Repeater

Manufactured by Hanwell | Ellab RoHS

Version 2 - EC190194

**Disclaimer:** The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product may be changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales@hanwell.com

# Sensor (supplied with unit)

Internal temperature sensor	Precision Thermistor
Operating temperature range	-10°C to +55°C (restricted by instrument operating range)
Accuracy	+/- 0.3°C
Long term drift	< 0.1°C per year