

RL4411 transmitter

Pro 4000T Series

Part of the **Hanwell Pro** RL4000T Series, the RL4411 is a temperature transmitter for 4 wire PT100 sensors, 5 pin Lemo socket and includes LCD display and 434.075MHz frequency as standard.

Features

- ✓ Single Channel PT100 instrument
- ✓ LCD display with data readings & battery life
- ✓ Superior performance hardware & high accuracy sensors
- ✓ Easily accessible battery & USB socket
- ✓ Low power radio for long distance transmission (3km over open ground)
- ✓ Complies with RoHS, EU & WEEE directives
- ✓ Carries CE Marking

Typical Applications

- Fridges
- Freezers
- Chillers


Always ask for a long-range signal strength test.



We can prove ours to be unrivalled.



Photo shows RL4411-434.075 (single channel unit)
Other frequencies are available



Instrumentation specification	
Dimension (Excl. ancillaries)	110 x 80 x 35mm
Weight	200 grams
Power supply	3.6V AA Lithium battery
Battery life	Up to 2 years (dependent on conditions of use and instrument settings)
Case material	ABS & PC
Memory capacity	100,000 readings single channel unit Unit will wrap when full
Clock accuracy (logging)	20 ppm at 25°C
Instrument measuring range	-200°C to +160°C (Dependent on probe selection)
Instrument operating range	-20°C to +60°C (non-condensing RH environment)
Instrument storage temperature	-40°C to +60°C
IP Rating	IP30
Unit accuracy	- +/- 0.1°C between 0°C to +40°C and +/-0.3°C outside these extremes
Resolution	0.1°C

Accessories	
J237	PT100 probe. Please refer to the Hanwell Pro Sensor datasheet
Y119	Wall mounting bracket
88706	AA Lithium battery

Radio transmitter functions	
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.
Radio power	10mW
Radio range	3km over open ground
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Software compatibility	EMS - All Versions Synergy - All Versions Important: Unit <i>Must</i> be synchronised to work
Hardware required	CR2 / CR3 – Controller SR2 – Smart Receiver REP – Repeater