

RL4411 transmitter

Pro 4000T Series

Part of the Hanwell Pro RL4000T Series, the RL4411 is a temperature transmitter for 4 wire PT100 sensors, 5 pin Lemo socket and includes LCD display and 434.075MHz frequency as standard.

Features

- √ Single Channel PT100 instrument
- √ LCD display with data readings & battery life
- √ Superior performance hardware & high accuracy sensors
- √ Easily accessible battery & USB socket
- √ Low power radio for long distance transmission (3km over open) ground)
- √ Complies with RoHS, EU & WEEE directives
- √ Carries CE Marking

Typical Applications

- Fridges
- Freezers
- Chillers

Always ask for a long-range signal strength test.



We can prove ours to be unrivalled.

Instrumentation specification		
Dimension (Excl. ancillaries)	110 x 80 x 35mm	
Weight	200 grams	
Power supply	3.6V AA Lithium battery	
Battery life	Up to 2 years (dependent on conditions of use and instrument settings)	
Case material	ABS & PC	
Memory capacity	100,000 readings single channel unit Unit will wrap when full	
Clock accuracy (logging)	20 ppm at 25°C	
Instrument measuring range	-200°C to +160°C	
Instrument operating range	-20°C to +60°C (non-condensing RH environment)	
Instrument storage temperature	-40°C to +60°C	
IP Rating	IP30	
Unit accuracy	- +/- 0.1°C between 0°C to +40°C and +/-0.3°C outside these extremes	
Resolution	0.1°C	









Photo shows RL4411-434.075 (single channel unit) Other frequencies are available

Accessories	
J237	PT100 probe. <u>Please refer to the Hanwell Pro</u> <u>Sensor datasheet</u>
Y119	Wall mounting bracket
88706	AA Lithium battery

Radio transmitter functio	ns
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.
Radio power	10mW
Radio range	3km over open ground
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Hardware required	CR2 / CR3 – Controller SR2 – Smart Receiver REP – Repeater

Manufactured by Hanwell | Ellab (€ 🗵 RoHS