

RL4512 transmitter

Pro RL4000CO₂ Series

Part of the **Hanwell Pro** RL4000RHT Series, the RL4512 combines CO₂ and temperature using high accuracy external sensors. The instrument includes LCD display and 434.075MHz frequency as standard.

Features

- ✓ Combined CO₂ and temperature measurement
- ✓ LCD display with 50,000 data readings per channel
- ✓ Superior performance hardware & high accuracy sensors
- ✓ Low power radio for long distance transmission (3km over open ground)
- ✓ Complies with RoHS, EU & WEEE directives
- ✓ Carries CE Marking

Typical Applications

- Laboratory incubators

Always ask for a long-range signal strength test.



We can prove ours to be unrivalled.



Carbon Dioxide



Temperature



Radio transmitter



Product code: RL4512-434.075

Instrumentation specification	
Dimension (Excl. ancillaries)	110 x 80 x 35mm
Weight	200 grams
Power supply	External 12V DC
Case material	ABS & PC
Battery	3.6V Half AA (The battery should only be used for downloading data from the unit and setting up of the unit.)
Memory capacity	50,000 readings per channel (unit will wrap when full)
Clock accuracy (logging)	20 ppm @ 25°C
IP Rating	IP30
Resolution	0.1°C
Instrument measuring range	-40°C to +60°C
Instrument operating range	-20°C to +60°C in a non-condensing RH environment
Instrument storage temperature	-40°C to +60°C
Unit accuracy	+/- 0.1°C

Radio transmitter functions	
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.
Radio power	10mW
Radio range	3km over open ground
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Hardware required	SR2 – Smart Receiver REP – Repeater

Product codes	
Y119	Wall mounting bracket
Probe options	Please refer to the Hanwell Pro Sensor datasheet

Manufactured by Hanwell | Ellab RoHS

Version 4 - EC190194

Disclaimer: The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product may be changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales@hanwell.com